

**POLYFLOR 2000 PUR**



2.0mm  
2.5mm



2m x 20m = 40m<sup>2</sup>  
2m x 15m = 30m<sup>2</sup>



300 x 300mm  
4.5m<sup>2</sup>  
3.6m<sup>2</sup>



608 x 608mm  
5.17m<sup>2</sup>  
-



3550g/m<sup>2</sup>  
4552g/m<sup>2</sup>



**GENERAL PERFORMANCE**  
EN 649 / EN ISO 10581  
ASTM F1913  
ASTM F1700



**REACTION TO FIRE**  
EN 13501-1 Class Bfl-S1  
ASTM E662<sup>†</sup> <450  
ASTM E648<sup>†</sup> Class 1



**SLIP RESISTANCE**  
EN 13893 Class DS  
AS/NZS 4586 R9



**ABRASION RESISTANCE**  
EN 660-2 Group M  
EN ISO 10581 Type II



**ELECTRICAL BEHAVIOUR**  
(body voltage)  
EN 1815 ≤2kV  
Classified as 'antistatic'



**MARITIME USAGE**  
American Bureau of Shipping<sup>†</sup>  
US Coast Guard Approved  
Marine Equipment Directive<sup>†</sup>  
96/98/EC  
SOLAS 74



**INDENTATION RESIDUAL**  
ASTM F970 (Modified)  
Static load 750psi



**CASTOR CHAIR**  
(continuous use)  
Suitable



**RESPONSIBLE SOURCING**  
BES 6001 Very Good



**VOC EMISSIONS**  
Indoor Air Comfort GOLD Eurofins certified product  
AgBB VOC test: Pass  
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)  
Finnish M1 Classification:<sup>†</sup> Pass  
Swedish B.P.D (FLEC test):<sup>†</sup> Best Class  
GBCA/NZGBC Green Star IEQ-VOC:<sup>†</sup> Compliant



**HYGIENE**  
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



**ENVIRONMENTALLY PREFERABLE FLOORING**  
Polyflor 2000 PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is Green Tag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. 2000 PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/environment](http://www.polyflor.com/environment)



Polyflor 2000 PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



**APPLICATIONS**  
Polyflor 2000 PUR is especially recommended for hospitals, schools, offices, supermarkets and institutional buildings, where an easy to maintain, hardwearing floorcovering with an attractive, modern appearance is required.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

†2.0mm

**POLYFLOR LTD.** PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)



**POLYFLOR**  
**2000 PUR**  
HOMOGENEOUS



**PERFORMANCE AND PROPERTIES**



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

